Issued: 23-10-2023 Valid until: 21-01-2026 Replaces: 0960-CPR-SKGIKOB.012120.01.ENG

Issued: 21-01-2021



Certificate holder

Byldis Facades BV De Run 4225 5503 LM Veldhoven

T: +31 (0)402 307 474 E: facades@byldis.com I: www.byldis.com

Certificate of constancy of performance

Declaration of SKG-IKOB (Notified Body 0960)

In compliance with Regulation (EU) No 305/2011 of the European Parliament and of the Council of 9 March 2011 (the Construction Products Regulation or CPR), this certificate applies to the construction product

EXTERNAL PEDESTRIAN DOORSETS IN ESCAPE ROUTES

as specified in the attached appendix placed on the market under the name or trade mark of the holder of this certificate and produced by the holder of this certificate or for the holder of this certificate in the manufacturing plant(s) if mentioned above.

This certificate attests that all provisions concerning the assessment and verification of constancy of performance described in Annex ZA of the standard(s)

EN 14351-1:2006+A2:2016

under system 1 for the performance set out in this certificate are applied and that the factory production control conducted by the manufacturer is assessed to ensure the constancy of performance of the construction product.

This certificate was first issued on 21-01-2021 and will remain valid until the date as mentioned at this certificate as long as neither the harmonised standard, the construction product, the AVCP methods nor the manufacturing conditions in the plant are modified significantly, unless suspended of withdrawn by the notified product certification

For SKG-IKOB

ir. H.A.J. van Dartel Certification manager

The users of this certificate are advised to verify at www.skgikob.nl if this certificate is still valid and actual. This certificate consists of 2 pages.



SKG-IKOB Certificatie Poppenbouwing 56 4191 NZ Geldermalsen

Postbus 202 4190 CE Geldermalsen

T 088-2440100 www.skgikob.nl Byldis Facades BV Number: 0960-CPR-SKGIKOB.012120.02.ENG

Appendix 1 CERTIFICATE OF CONSTANCY OF PERFORMANCE

Specification	Characteristic	Classification
Product type: External pedestrian doorsets in escape routes Material: aluminium	Ability to release	According to EN 179, EN 1125, EN 1935, prEN 13633 or prEN 13637
System: aluminium (door) profile systems		

Note 1:

Lever operated escape doors are subjected to the requirements of EN 179. Escape doors with a pushbar are subjected to the requirements of EN 1125.

Note 2

Products, intended to realise the ability to release in relation to escape doors, provided with a valid CE-marking, assembled and installed in accordance with the installation instructions provided by the manufacturer of the product, met the conditions for delivery under this certificate of constancy of performances. Provided that the performances in the CE-marking are adequate according to the requirements and regulations in the member state of the European Union.